


MONOFOCAL

MODEL NUMBER	MX60E	MX60PL			
SKUS FOR ORDERING IN US	MXUE	MXUEPL			
	(+Spherical Power)	(+Spherical Power)			
INJECTORS (2.4mm incision size)					
BLIS Injector System	✓				
INJ100	✓				
SimplifEYE Delivery System		✓			
DIOPTER RANGE	0 to +10D in 1.0D increment				
	+10D to $+30D$ in $0.5D$ increments				
	+30D to +34D in 1.0D increments				
OPTIC SIZE	6mm				
OPTIC LENGTH	12.5mm				
HAPTICS	Modified C, fenestrated				
OPTIC DESIGN	Aspheric				
	Abberation-free				
	Biconvex				
OTHER FEATURES	Glistening Free-hydrophobic acrylic material				
	Refractive Index: 1.53 at 35° C				
	UV absorbing Sharp 360° square posterior edge				
ODTICAL BIOMETRY					
OPTICAL BIOMETRY		Constant*: 119.1 nstant: 5.61			
	Surgeon Factor: 1.85mm				
	Barrett Lens Factor: 1.94mm				
	Barrett Lens Desi	gn Factor: -0.50D			
APPLANATION	Suggested A (Constant*: 118.7			
	Surgeon Factor: 1.62mm				
	ACD-Const	tant: 5.37mm			


LENS SPECIFICATIONS



Important Safety Information for enVista® Preloaded IOL & enVista Toric Preloaded IOL (Model MX60PL & MX60PT) with SimplifEYE® Inserter INDICATIONS: The enVista one-piece hydrophobic acrylic IOL (Model MX60PL) is indicated for primary implantation in the capsular bag of the eye in adult patients for visual correction of aphakia following removal of a cataractous lens for improved uncorrected distance vision. The enVista one-piece hydrophobic acrylic toric IOL (Model MX60PT) is indicated for primary implantation in the capsular bag of the eye in adult patients for visual correction of aphakia and corneal astignmatism following removal of a cataractous lens for improved uncorrected distance vision. The Simpliff YE® Inserter is indicated for folding and inserting of enVistal OLs (Models MX60PL) and MX60PT and IOL models approved for use with this IOL insertion device. WARNINGS: Careful preoperative evaluation and sound clinical judgment should be used by the surgeon to decide the risk / benefit ratio before implanting a lens in a patient. PRECAUTIONS: Do not resterilize this intraocular lens or inserter by any method. Do no use if the packaging is damaged or if there are signs of leakage. Do not store lenses or inserter at temperatures over 43°C (109°F) or lower than 0°C (32°F). Do not resterilize the insirt properative evaluation and intraoperative complications as outlined in the Directions for Use. ADVERSE EVENTS: As with any surgical procedure, there is risk involved. Potential complications accompanying cataract or implant surgery may include, but are not limited to the following: corneal endothelial damage, infection (endophthalmitis), retinal detachment, vitritis, cystoid macular edema, corneal edema, pupillary block, cyclitic membrane, iris prolapse, hypopyon transient or persistent glaucoma, acute corneal decompensation, toxic anterior segment syndrome (TASS), and secondary surgical intervention. CAUTION: Federal law restricts this device to sale by or on the order of a physician. ATTENTION: Reference th



LENS SPECIFICATIONS _____



MODEL NUMBER	MX60ET	MX60PT			
SKUS FOR ORDERING IN US	MXUET (+Cylinder +Spherical Power)	MXUPT (+Cylinder +Spherical Power)			
INJECTORS (2.4mm incision size)					
BLIS Injector System	1				
INJ100	✓				
SimplifEYE Delivery System		√			
DIOPTER RANGE	+6D to $+30D$ in $0.5D$ increments				
OPTIC SIZE	6mm				
OPTIC LENGTH	12.5mm				
HAPTICS	Modified C, fenestrated				
OPTIC DESIGN	Aspheric Abberation-free Biconvex (posterior toricity for MX60ET & MX60PT)				
OTHER FEATURES	Glistening Free-hydrophobic acrylic material Refractive Index: 1.53 at 35° C UV absorbing Sharp 360° square posterior edge				
OPTICAL BIOMETRY	Suggested A Constant*: 119.1 ACD-Constant: 5.61 Surgeon Factor: 1.85mm Barrett Lens Factor: 1.94mm Barrett Lens Design Factor: -0.50D				
APPLANATION	Suggested A Constant*: 118.7 Surgeon Factor: 1.62mm ACD-Constant: 5.37mm				

TORIC

CYLINDER POWER CYLINDER POWER								
IOL Plane	1.25	2.00	2.75	3.50	4.25	5.00	5.75	
Corneal Plane	0.90	1.40	1.93	2.45	2.98	3.50	4.03	
Range of Predicted Postoperative Corneal Cylinder	0.77-1.39	1.40-1.92	1.93-2.44	2.45-2.97	2.98-3.49	3.50-4.02	4.03-4.53	